


ČELIČNA UŽAD

ČELIČNA UŽAD OPĆE NAMJENE



Šifra	Promjer užeta mm	Težina kg/100m		Min. prekidna sila (kN)			
				Čvrstoća žice (N/mm ²)			
				1570		1770	
		KJ	ČJ	KJ	ČJ	KJ	ČJ
19151	6	12.6	13.9	18.8	20.3	21.2	22.9
19152	7	17.2	19.0	25.5	27.6	28.8	31.1
19153	8	22.5	24.8	33.4	36.1	37.6	40.7
19154	9	28.4	31.3	42.2	45.7	47.6	51.5
19155	10	35.1	38.7	52.1	56.4	58.8	63.5
19156	11	42.5	46.8	63.1	68.2	74.1	76.9
19157	12	50.5	55.7	75.1	81.2	84.6	91.5
19158	13	59.3	65.4	88.1	95.3	99.3	107
19159	14	68.8	75.9	102	110	115	125
19160	16	89.9	99.1	133	144	150	163
19161	18	114	125	169	183	190	206




6X7+KJ

DIN 3055 - HRN C.H1.070

Primjena: opća namjena,
Nije za dizanje.
Konstrukcija: 6x7 +KJ
Završna obrada: Pocičano



Šifra	Promjer užeta mm	Težina kg/100m		Min. prekidna sila (kN)			
				Čvrstoća žice (N/mm ²)			
				1570		1770	
		KJ	ČJ	KJ	ČJ	KJ	ČJ
19171	6	12.6	14.4	17.4	18.8	19.6	21.2
19172	7	17.2	19.36	23.6	25.5	26.6	28.8
19173	8	22.5	25.6	30.8	33.4	34.8	37.6
19174	9	28.4	32.4	39.0	42.2	44.0	47.6
19175	10	35.4	40.0	48.2	52.1	54.4	58.8
19176	11	42.5	48.4	58.3	63.1	65.8	71.1
19177	12	50.5	57.6	69.4	75.1	78.2	84.6
19178	13	59.3	67.6	81.5	88.1	91.8	99.3
19179	14	68.8	78.4	94.5	102	107	115
19180	16	89.9	102	123	133	139	150
19181	18	114	130	156	169	176	190
19182	20	140	160	193	208	217	235
19183	22	170	194	233	252	263	284
19184	24	202	230	278	300	313	338
19185	26	237	270	326	352	367	397
19186	28	275	314	378	409	426	461




6X19+ČJ

DIN 3060 - HRN C.H1.072

Primjena: opća namjena,
plovni bageri, voćnjaci...
Konstrukcija: 6x19
Završna obrada: Pocičano
ili maščeno.




Šifra	Promjer užeta mm	Težina kg/100m		Min. prekidna sila (kN)			
				Čvrstoća žice (N/mm ²)			
				1570		1770	
		KJ	ČJ	KJ	ČJ	KJ	ČJ
19201	8	26.1	25.6	29.6	32.1	33.4	36.1
19202	9	28.0	32.4	37.5	40.6	42.3	45.7
19203	10	34.6	40.0	46.3	50.1	52.2	56.5
19204	11	41.9	48.4	56.0	60.6	63.21	68.3
19205	12	49.8	57.6	66.7	72.1	75.2	81.3
19206	13	58.5	67.6	78.3	84.6	88.2	85.4
19207	14	67.8	78.4	90.8	98.2	102	111
19208	16	88.6	102	119	128	134	145
19209	18	112	130	150	162	169	183
19210	20	138	160	185	200	209	226
19211	22	167	194	224	242	253	273
19212	24	199	230	267	288	301	325
19213	26	234	270	313	339	353	382
19214	28	271	314	363	393	409	443
19215	30	311	360	447	451	470	508
19216	32	354	410	474	513	535	578
19217	34	400	462	535	579	604	653
19218	36	448	518	600	649	677	732



6X37+KJ

DIN 3066 - HRN C.H1.074


Primjena: opća namjena
čelične priveznice, kranovi.
Konstrukcija: 6x37
Završna obrada: Pocičano,
ili maščeno.




ČELIČNA UŽAD

ČELIČNA UŽAD NEROTIRAJUČA

Šifra	Promjer užeta mm	Težina		Min. prekidna sila(kN)			
				Čvrstoća žice(N/mm ²)			
				kg/100m		1770	
KJ	ČJ	KJ	ČJ	KJ	ČJ		
19451	16	99.8	110	124	128	140	144
19452	18	126	139	157	162	177	182
19453	20	156	172	193	200	218	225
19454	22	189	208	234	242	264	272
19455	24	225	248	279	288	314	324
19456	26	264	291	327	337	369	380
19457	28	306	337	379	391	427	441
19458	30	351	387	435	449	491	507
19459	32	399	440	495	511	558	576




36x7+KJ



36x7+ČJ


DIN 3072 - HRN C H1.119

Primjena: dizalice, kranovi
Završna obrada: Pocičano,
crno-mašćeno



ČEL. UŽAD

Šifra	Promjer užeta mm	Težina kg/100m	Čvrstoća žice (N/mm ²)				
			Min. prekidna sila(kN)				
			1570	1670	1770	1870	1960
19471	13	67.9	85.4	90.1	95.2	100.2	104.0
19472	14	78.8	111	118	125	132	138
19473	16	118	145	154	163	172	181
19474	18	149	183	195	206	218	229
19475	20	184	226	240	255	269	282
19476	22	223	274	291	308	326	342
19477	24	265	326	346	367	388	406
19478	26	311	382	406	431	455	(477)
19479	28	361	443	471	500	(528)	(553)
19480	30	414	509	541	573	(606)	(635)
19481	32	471	579	616	(652)	(689)	(723)



35Wx7

DIN 3072 - HRN C.H1.118

Primjena: dizalice, kranovi
Završna obrada: Pocičano,
crno-mašćeno
Moguća isporuka
u ovoj konstrukciji: 10mm, 11mm,
12mm, 15mm, 17mm, 19mm

